

UniSource Energy, Inc. Specialty Petroleum Products Typical Properties			
Supplier Name			<b>UNISOURCE</b>
Product Name			<b>UNIPAR®</b>
			<b>SH 260 CC</b>
<b>Test Description</b>	<b>ASTM NO.</b>		
Specific gravity @ 60°F	D 1250		0.834
Gravity, API @ 60°F	D 287		38.1
Density (Lb/Gal) @ 60°F			6.94
Color, Saybolt	D 156		+30
Viscosity,	D 445		
SSU @ 104°F			40.2
SSU @ 210°F			
cSt @ 40°C			4.3
cSt @ 100°C			
GC Distillation Points, F (°C)	D 86		
IBP			530 (277)
5%			536 (280)
10%			537 (281)
50%			555 (291)
90%			589 (309)
95%			596 (313)
EP			615 (324)
Kauri Butanol	D 1133		23.8
Aniline point, F (°C)	D 611		187 (86)
Flash point, PMCC, F (°C)	D 93		280 (138)
Pour point, F (°C)	D 97		-40 (-40)
Refractive Index @ 68 F	D 1218		1.4571
Sulfur, ppm	D 5453		< 1
Aromatics, SFC, %			< 0.5
Chemical Abstract #			64742-46-7
			Oct-07

The values shown here are representative of current production.  
Some are controlled by manufacturing specifications, while others are not.  
All may vary within modest ranges.