

UniSource Energy, Inc. Specialty Petroleum Product Typical Properties			
Supplier Name			UNISOURCE
Product Name			UNIPAR®
			SH 340 CC
Test Description	ASTM NO.		
Specific gravity @ 60°F	D 287		0.86
Gravity, °API @ 60°F			33.1
Density (Lb/Gal) @ 60°F			7.16
Viscosity,			
SSU @ 100°F	D 445		55.7
SSU @ 210°F			
cSt @ 40°C			8.5
cSt @ 100°C			
Distillation Range, °F (°C)	D 86		
IBP			590 (311)
5%			610 (321)
10%			615 (324)
50%			625 (329)
90%			640 (338)
95%			645 (341)
EP			660 (349)
Kauri Butanol	D 1133		22.4
Aniline point, °F (°C)	D 611		195 (90)
Flash point, COC, °F (°C)	D 92		330 (166)
Pour point, °F (°C)	D 97		-40 (-40)
Refractive Index, 20 °C (68 °F)	D 1218		1.4695
Sulfur, ppm	D 5453		<1
Aromatics, SFC, %	SFC		< 0.5
Saturates, SFC, %			>99.5
Chemical Abstract #			64742-46-7
			Oct-07

The values shown here are representative of current production.
Some are controlled by manufacturing specifications, while others are not.
All may vary within modest ranges.