

UniSource Energy, Inc.
Specialty Paraffinic Oil
Typical Properties



Supplier Name	UNISOURCE
Product Name	UNIPAR® 580 CC

Test Description	ASTM NO.	
Specific Gravity @ 60°/60°F	D 4052	0.8749
Gravity, °API @ 60°F	D 4052	30.2
Density (Lb/Gal) @ 60°F	D 4052	7.28
Color, ASTM	D 1500	L 0.5
Viscosity, SSU @ 100°F	D 2161	553
Viscosity, SSU @ 210°F	D 2161	68
Viscosity, cSt @ 40°C	D 445	106.0
Viscosity, cSt @ 100°C	D 445	11.8-12.6
Viscosity-Gravity Constant	D 2501	0.797
Aniline Point, °F (°C)	D 611	241 (116)
Pour Point, °F (°C)	D 5949	10 (-12)
Flash Point, °F (°C)	D 92	514 (268)
Composition %:	D 5186	
Saturates		99
Aromatics		0
Polar Compounds		0
Sulfur, ppm	D 1552	<1

Chemical Abstract #	64742-54-7 Dec-11
---------------------	----------------------

*The values shown here are representative of current production.
Some are controlled by manufacturing specifications, while others are not.
All may vary within modest ranges.*