

| UniSource Energy, Inc. | | | |
|--|----------|--|------------------|
| Specialty Petroleum Product | | | |
| Specifications and Typical Inspections | | | |
| Supplier Name | | | UNISOURCE |
| Product Name | | | UNIPAR® |
| | | | 70 TOM |
| Test Description | ASTM NO. | | |
| Specific Gravity @ 60°/60°F | D 1298 | | 0.8438 |
| Gravity, °API @ 60°F | D 4052 | | 36.2 |
| Density (Lb/Gal) @ 60°F | | | 7.04 |
| Color, ASTM | D 1500 | | 0.5 |
| Viscosity, SSU @ 100°F | | | 70 |
| Viscosity, SSU @ 210°F | | | |
| Viscosity, cSt @ 40°C | D 445 | | 12.0 |
| Viscosity, cSt @ 100°C | | | 3 |
| Viscosity Index | D 2270 | | 104 |
| GC Distillation, Off @ 700 °F, % | D 2887 | | |
| Volatility, NOACK, wt. % | D 5800 | | |
| Pour Point, °F (°C) | D 5950 | | 5 (-15) |
| Flash Point, COC, °F (°C) | D 92 | | 374 (190) |
| Chemical Composition, Wt.% | | | |
| Aromatics | | | 1.5 |
| Sulfur, ppm | D 3120 | | < 15 |
| Chemical Abstract # | | | 64742-55-8 |
| | | | Oct-06 |

The values shown here are representative of current production.
Some are controlled by manufacturing specifications, while others are not.
All may vary within modest ranges.