

SECTION 1.0 PRODUCT AND COMPANY IDENTIFICATION	
--	--

Product Identifier

UNIPAR® 100 AV

Other means of identification

A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C_{20} through C_{50} and produces a finish oil with a viscosity of at least 100 SUS at 100°F (19 cSt at 40°C).

Recommended use (identified)

Base material for the production of various lubricating oils

Manufacturer/Importer/Supplier/Distributor Information

UNISOURCE-ENERGY, LLC 40 Shuman Blvd, Suite 290 Naperville, IL 60563

E-mail

orders@unisource-energy.com

Telephone number

Phone: 630-470-6030 Fax: 630-470-6031

Emergency telephone number

UNISOURCE-ENERGY, LLC

1-800-444-5510

CHEMTREC 1-800-424-9300

SECTION 2.0	HAZARD(S) IDENTIFICATION
-------------	--------------------------

OSHA/HCS status

Physical Hazards

Not classified

Health Hazards

Aspiration Hazard

OSHA Defined Hazards

Not classified



GHS label elements Hazard Symbol



Signal word

Danger

Hazard Statement

May be fatal if swallowed and enters airways.

Precautionary Statement

Prevention

Observe good industrial hygiene practices.

Response

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

SECTION 3.0 COMPOSITION/INFORMATION ON INGREDIENTS
--

Chemical name


Paraffin oils (petroleum), catalytic dewaxed heavy

CAS number/other identifiers

Ingredient Name	%	CAS number
Paraffin oils (petroleum), catalytic dewaxed heavy	100	64742-70-7

Composition Comments

IP346 method DMSO extract for base oil substances: <3.0%.



SECTION 4.0	FIRST AID MEASURES

Description of necessary first aid measures

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

Inhalation

Move to fresh air. If breathing is difficult, give oxygen. Get medical attention, if needed.

Skin contact

Remove contaminated clothing and shoes. Wash off immediately with soap and plenty of water. Get medical attention if irritation develops or persists. Wash clothing separately before reuse. Destroy or thoroughly clean contaminated shoes. If high pressure injection under the skin occurs, always seek medical attention.

Ingestion

Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Get medical attention immediately.

Most important symptoms, acute and delayed

Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

Get medical attention if symptoms occur. Show this safety data sheet to the doctor in attendance.

SECTION 5.0 FIRE-FIG	GHTING MEASURES
----------------------	-----------------

Suitable extinguishing media

Water spray. Water fog. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the chemical

The product is not flammable. Will burn if involved in a fire.

Special protective equipment and precautions for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.



Fire Fighting equipment/instructions

Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do it without risk. In the event of fire, cool tanks with water spray. Cool containers exposed to flames with water until well after the fire is out. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Water runoff can cause environmental damage. Use compatible foam to minimize vapor generation as needed.

General fire hazards

This product is not flammable. Will burn if involved in a fire.

SECTION 6.0	ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. In case of spills, beware of slippery floors and surfaces. See Section 8 of the SDS for Personal Protective Equipment.

Environmental precautions

Contain spillages with sand, earth or any suitable adsorbent material. Prevent spillage entering a watercourse or sewer, contaminating soil or vegetation. If this is not possible, notify police and appropriate authorities immediately.

Methods and materials for containment and cleaning up

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination Large Spills: Prevent entry into waterways, sewers, basements or confined areas. If necessary dike the product with dry earth, sand or similar non-combustible materials. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Clean surface thoroughly to remove residual contamination


SECTION 7.0 HANDLING AND STORAGE	
----------------------------------	--

Precautions for safe handling

Keep away from heat, spark, open flames and other sources of ignition. Avoid prolonged or repeated contact with skin. Be aware of potential for surfaces to become slippery.

Conditions for safe storage, including any incompatibilities

Store in a dry place. Keep away from incompatible materials, open flames and high temperatures.



SECTION 8.0	EXPOSURE CONTROLS/PERSONAL PROTECTION
-------------	---------------------------------------

Occupational exposure limits

US. OSHA Table Z-	1 Limits for Air Conta	minants (29 CFR 191	0.1000)
Components	Туре	Value	Form
Oil Mist, mineral	PEL	5 mg/m ³	Mist
(CAS -)	TWA	5 mg/m ³	Inhalable fraction
US. NIOSH: Pocket	Guide to Chemical H	azards	
Oil Mist, mineral	STEL	10 mg/m ³	Mist
(CAS -)	TWA	5 mg/m ³	Mist

Biological limit values

No biological exposure limits noted for the ingredient(s)

Engineering measures

Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

Personal protective equipment

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Hand protection

Chemical/oil resistant gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Eye protection

Wear safety glasses. If splash potential exists, wear full face shield or chemical goggles.

Other


Normal work clothing (long sleeved shirts and long pants) is recommended.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.



SECTION 9.0 PH	YSICAL AND CHEMICAL PROPERTIES
----------------	--------------------------------

Physical stateLiquidColorAmberOdorMild

Odor thresholdNot availablepHNot applicableMelting point/freezing pointNot applicablePour Point24.8°F (-4°C)

Initial boiling point and boiling range >600.8 °F (> 316 °C)

Flash point >300.2 °F (> 149.0 °C) ASTM D-92

Evaporation rateNot available **Flammability (solid, gas)**Not applicable

Lower explosive (flammable) limits >0.6% Upper explosive (flammable) limits <7%

Vapor pressure < 0.1 mm Hg (20°C)

Vapor density >2

Relative density
Solubility (water)
Not available
Insoluble

Partition coefficient n-octanol/water
Auto-ignition temperature

Decomposition temperature

Viscosity

Not available
19 mm²/s (40°C)
Explosive properties

Not available
19 mm²/s (40°C)
Not explosive

Molecular formula UVCB

Oxidizing properties Not oxidizing

SECTION 10.0 STABILITY AND REACTIVITY

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Stable under normal temperature conditions and recommended use.

Possibility of hazardous reactions

Hazardous polymerization does not occur.



Conditions to avoid

Contact with incompatible materials. Do not pressurize, cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

Carbon oxides. Sulfur oxides. Hydrocarbons.

SECTION 11.0	TOXICOLOGICAL INFORMATION

Information on the likely routes of exposure

Inhalation

Inhalation of oil mist or vapors formed during heating of the product will irritate the respiratory system and provoke coughing.

Skin contact

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eve contact

Direct contact with eyes may cause temporary irritation.

Ingestion

Swallowing or vomiting of the liquid may result in aspiration into the lungs. Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms may include redness, drying and cracking of the skin. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Information on toxicological effects

Acute toxicity

Human evidence indicates that the product has very low acute oral, dermal or inhalation toxicity. However, it can produce severe injury if taken into the lung as a liquid, and there may be profound central nervous system depression following prolonged exposure to high levels of vapor.

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation

Serious eye damage/eye irritation

Direct contact with eyes may cause temporary irritation.



Respiratory or skin sensitization

Respiratory sensitization

Not classified

Skin sensitization

Not classified

Germ cell mutagenicity

Not classified

Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Not classifiable as to carcinogenicity to humans. (3)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Reproductive toxicity

Not classified

Specific target organ toxicity -single exposure

Not classified

Specific target organ toxicity -repeated exposure

Not classified

Aspiration hazard

May be fatal if swallowed and enters airways.

Further information

Symptoms may be delayed. Pre-existing skin conditions including dermatitis might be aggravated by exposure to this product.

SECTION 12.0	ECOLOGICAL INFORMATION
020110111210	

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

The product is expected to be slowly biodegradable.

Bioaccumulative potential


The product is not expected to bioaccumulate.

Mobility in soil

No data available.

Mobility in general

The product is insoluble in water.



Other adverse effects

Oil spills are generally hazardous to the environment.

SECTION 13.0	DISPOSAL CONSIDERATIONS

Disposal instructions

Recover and recycle, if practical. Dispose in accordance with all applicable regulations.

Hazardous waste code

Waste codes should be assigned by the user based on the application for which the product was used

Waste from residues / unused products

Dispose in accordance with applicable federal, state, and local regulations.

Contaminated packaging

Dispose of empty containers according to applicable federal, state/provincial and/or local regulations.

SECTION 14.0	TRANSPORT INFORMATION
--------------	-----------------------

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL, 73/78 and the IBC code

Not applicable. However, this product is a liquid and if transported in bulk covered under MARPOL 73/78, Annex I.

SECTION 15.0	REGULATORY INFORMATION

OSHA/HCS status

This product is hazardous according to OSHA 29CFR 1910.1200.

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpart. D)

Not regulated



OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed

SARA 311/312 Hazardous chemical

Yes

SARA 313 (TRI reporting)

Not regulated.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated

Safe Drinking Water Act (SDWA)

Not regulated

US State Regulations

Massachusetts RTK - Substance List

Mineral Oil, highly refined (CAS -)

Oil Mist, mineral (CAS -)

New Jersey Worker and Community Right-to-Know Act

Mineral Oil, highly refined (CAS -)

Oil Mist, mineral (CAS -)

Pennsylvania Worker and Community Right-to-Know Law

Oil Mist, mineral (CAS -)

Paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7)

Rhode Island RTK

Not regulated

California Proposition 65

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



International regulations

National Inventory

Country(s) or region	Inventory	On inventory (yes/no) *
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventor	Yes


^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16.0 OTHER INFORMATION

Further information	
Japan: MITI ENCS Number (9)-1692	



NFPA rating



Abbreviations

ACGIH = American Conference of Governmental Industrial Hygienists; ADR = European Road Transport; AICS = Australia Inventory of Chemical Substances; ASTM = American society of Testing and Materials; ATE = Acute Toxicity Estimation: AU = Australia: Autoignition Temperature = The minimum temperature required to initiate combustion in air with no other source of ignition, BCF = Bioconcentration Factor; BEI = - Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV, BEL = Biological exposure limits: BOD = Biochemical Oxygen Demand: BTEX = Benzene, Toluene, Ethylbenzene, Xylenes; C = Celsius, CA = Canada, CAS = Chemical Abstracts Service; CEFIC = European Chemical Industry Council; CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; CLP = Classification Packaging and Labelling Regulation (Regulation (EU) No. 1272/2008; COC = Cleveland Open Cup; CN = China; CPR= Controlled Products Regulations; CWA = Clean Water Act; DEA - Drug Enforcement Administration; DFG = Deutsche Forschungsgemeinschaf; DIN = Deutsches Institut für Normung; DMEL = Derived Minimal Effect Level; DNEL = Derived No Effect Level; DOT = Department of Transportation; DSL = Domestic Substances List (Canada); EC = European Commission; EC50 = Effective Concentration fifty; ECC = European Economic Community; ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals; ECHA = European Chemicals Agency; EINECS - European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EL50 = Effective Loading fifty; ENCS = Japan Existing and New Chemical Substances; EPA = Environmental Protection Agency; EU = European Union; EUH statement = CLP -specific Hazard statement: EWC = European Waste Code: F = Fahrenheit; Flash Point = Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. GHS = Globally Harmonized System of Classification and Labelling of Chemicals; HAPs = Hazardous Air Pollutants; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; IBC = Intermediate Bulk Container; IC50 = Inhibitory Concentration fifty; ICAO = International Civil Aviation Organization; IDL = Ingredient Disclosure List; IDLH = Immediately Dangerous to Life and Health; IL50 = Inhibitory Level fifty; IMDG = International Maritime Dangerous Goods; INSHT = National Institute for Health and Safety at Work; INV = Chinese Chemicals Inventory; IOPC = International Oil Pollution Compensation; IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables; JP - Japan; , Kow = Octanol/water partition; KECI = Korea Existing Chemicals Inventory, LC₅₀ = Lethal Concentration (gases) which kills 50% of the exposed animals, LD50 = :Lethal Dose (solids & liquids) which kills 50% of the exposed animals; . LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading; LL₅₀ = Lethal Loading fifty; LEL = The lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.; LogPow = logarithm of the octanol/water partition coefficient; LOLI = List of LIsts™ - ChemADVISOR's Regulatory Database: MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978, ("Marpol" = marine pollution: MAK = Maximum Concentration Value in the Workplace: MEL = Maximum Exposure Limits; mg/m³ = : Concentration expressed in weight of substance per volume of air, mg/kg = Quantity of material, by weight, administered to a test subject, based on their body weight in kg, NDSL = Non-Domestic Substances List (Canada); NE

UNISOURCE-ENERGY, LLC



SAFETY DATA SHEET

= Not Established; NFPA = National Fire Protection Association; NIOSH = National Institute for Occupational Safety and Health; NJTSR = New Jersey Trade Secret Registry; NOEC/NOEL = No Observed Effect Concentration / No Ob-served Effect Level; NTP = National Toxicology Program; NZ = New Zealand; OE_HPV = Occupational Exposure - High Production Volume; OSHA = U.S. Occupational Safety and Health Administration; PAH = Polycyclic Aromatic Hydrocarbon; PBT = Persistent, Bioaccumulative and Toxic; PEL = Permissible Exposure Limit (OSHA); PH= Philippines; PICCS = Philippines Inventory of Chemicals and Chemical Substances; ppm = Concentration expressed in parts of material per million parts of air or water, PMCC = Pensky Martin Closed Cup; PNEC = Predicted No Effect Concentration; RCRA = Resource Conservation and Recovery; REACH = Registration Evaluation And Authorization Of Chemicals: RID = European Rail Transport; RRN = REACH Registration Number: RQ = Reportable Quantity; RTECS = Registry of Toxic Effects of Chemical Substances®; RTK = Right To Know; SARA = Superfund Amendments and Reauthorization Act; SKIN DES = Skin Designation; STEL = Short Term Exposure Limit (15 minutes); SCBA = Self-Contained Breathing Apparatus; SDWA = Safe Drinking Water Act; STOT = Specific Target Organ Toxicity, TDLo, = the lowest dose to cause a symptom, TCLo = the lowest concentration to cause a symptom; TDo, LDLo, and LDo, or TC, TCo, LCLo, and LCo, the lowest dose (or concentration) to cause lethal or toxic effects, TDG = Transportation of Dangerous Goods; TLV = Threshold Limit Value (ACGIH); TRA = Targeted Risk Assessment; TSCA = Toxic Substances Control Act; TWA = Time Weighted Average (8 hours); UEL = The highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.; UN = United Nations; US = United States; UVCB = Unknown, of Variable Composition, or of Biological Origin; vPvB = very Persistent and very Bioaccumulative; WHMIS = Worker Hazardous Materials Information System (Canada)

Disclaimer

The information presented herein has been compiled from sources considered to be dependable and is accurate as of the date of preparation of this Safety Data Sheet. However, Seller does not assume any liability whatsoever for the accuracy or completeness of the information contained herein The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license. All materials may present unknown hazards and should be used with caution. In addition, no responsibility can be assumed by the Seller for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the material. Seller assumes no responsibility for injury to Buyer or to third persons or any damage to any property. Buyer assumes all such risks.